

~ ENGINEERED IN GERMANY ~

Regional Drive





Optimal footprint and even wear

Outstanding tyre mechanics optimization design and comprehensive optimization of tyre structure give GREENTRAC excellent tyre footprint which ensures even tread wear and longer mileage.

Super wide tread

Super wide tread width and deep grooves offer smooth drive and safe arrival.





High-density lateral grooves

High-density lateral grooves design makes every fuel consumption into powerful traction.

SIZE	PR/L	R LOAD INDEX / SPEED CODE	STANDA RIM		SECTION WIDTH	LOAD	PRESSURI (kpa/psi)	(mm/32nds)	TT/TL
295/60R22.5	16 / H	150/147 K (149/146 L)	9.00	926 / 36.5	292 / 11.5	3350/3075	900 / 130	21 / 26.5	TL
295/80R22.5	18 / J	152/148 M	9.00	1044 / 41.1	298 / 11.7	3550/3150	850 / 123	21 / 26.5	TL
315/70R22.5	18 / J	154/150 L	9.00	1014 / 39.9	312 / 12.3	3750/3350	900 / 130	22 / 27.7	TL
315/80R22.5	20 / L	156/150 L (154/150 M)	9.00	1076 / 42.4	312 / 12.3	4000/3350	850 / 123	22 / 27.7	TL